
PRODUCT DATASHEET

KunLun CF-4 HD Diesel Engine Oil

KunLun CF-4 HD Diesel Engine Oil is an economical and high quality crankcase oil developed to clean and protect older heavy duty diesel engines in markets requiring higher TBN.

PERFORMANCE STANDARDS

KunLun CF-4 HD Diesel Engine Oil meets the following performance requirements:

- API CF-4

BENEFITS

KunLun CF-4 HD Diesel Engine Oil provides the following benefits:

- Cost effective solution for older trucks.
- Removes existing carbon deposits and prevents agglomeration of soot.
- Protects against acid corrosion.
- Provides good anti-wear protection.
- Higher TBN to cope with severe fuel quality.

APPLICATIONS

KunLun CF-4 HD Diesel Engine Oil is recommended for use in high-speed four-stroke heavy duty diesel engines requiring API CF-4 or earlier classifications. It is especially recommended for use in older trucks (Euro 0 – II) to cope with severe fuel quality.



TYPICAL CHARACTERISTICS

KunLun CF-4 HD Diesel Engine Oil

SAE Grade	15W40	20W50
Kinematic Viscosity		
40°C, mm ² /s	116.5	174.1
100°C, mm ² /s	15.5	19.8
Viscosity, Apparent		
-15 °C, mPa·s	-	8300
-20 °C, mPa·s	6500	-
Viscosity Index	139	131
Specific Gravity, 15°C	0.874	0.883
Flash Point, COC, °C	236	252
Pour Point, °C	-33	-30
TBN, mgKOH/g	10.3	10.3
